



Acrylic Backing features:

- Superior thermal and noise insulation
- 100% Block out for light
- Mill guaranteed not to yellow over time due to premium acrylic used.
- Soft and pliable finish
- Does not self-adhere
- Workroom approved for problem free manufacturing
- Washable up to 10 washes (see new care label below)

Care Label 6W

For use on acrylic foam backed and flock coated fabrics of both man-made fibres and cotton. Regular care will minimize the need for additional cleaning. Gently vacuum with appropriate attachment. Always exercise caution when spot cleaning. Test clean on non-exposed surface. Avoid excessive rubbing and abrasion.

Remove hooks, rings and trims before cleaning.

Professional laundering recommended (Max 30 C).

Do not dry clean. ☒ Gentle machine or hand wash in cold water (Max 30 C). Mild detergents, such as wool mixes are recommended and ensure any detergent is fully dissolved. If washing by machine do not overfill load and limit washing time to 5 minutes or delicate cycle so coated sides do not touch each other for an extended period of time (ideally wash each drape separately).

Do not bleach, soak, rub or wring. Drip dry in shade. Immediately hang curtains by their hooks in an appropriate area that will not be damaged by water drops. Hang the drape with the header fully open until dry to avoid coated sides touching and shorten drying time. Do not use pegs or fold over clothesline. Curtains are heavy when wet.

Do not iron or press coated side. Cool iron with a damp cloth between the fabric and iron/press on fabric side only. Do not wash drapes excessively (no more than 10 washes) otherwise the backing will break down prematurely.

Possible shrinkage 3%.